THIS COPY IS PROVIDED	ON /	A RESTRICTED BASIS AND IS NOT TO BE L High Conductivity	ISED IN ANY W	AY DETRIMEN	TAL TO THE INTE	ITERESTS OF PANDUIT CORP.	
		Seamless Copper Tube					
Plating		Electro-Tin					
Wire Size		1/0 AWG				38 R Ref Color code	
Wire Type		Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric			LI 🐵 n	barrel markir	
Wire Strip Length		1.0 in.	.52±.04	$(+)$	NDU STR 0		
Stud Size		1/4 in.			PAI		
UL Listed Wire Connector		Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.		.32±.04 -	— 1.00±.02 –		
UL Temperature Rating		90°C		•		2.95±.06►	
C.S.A Certified Wire Connector		Yes					
Panduit Color Code on Barrel	е	PINK					
Panduit Die Index N on Barrel	No.	P42			Wire inco.	94±.04 - Beveled entry	
Alternate Industry Die Index No. () on Barrel		(12)			wie inspe	Dection window	±.01
CERT	B	LISTED .13 Wire Connector	±.01				_
						CORP. TINLEY PARK, ILLI	NOI
						LCDN1/0-14D-X	
		CHANGED BARREL MARK FROM PA		CDN1/0	PC00065	SCALE DRAWING NO / CAD FILE	
EV DATE BY CI	HK	DESCRIPT	ION		ECN	N/A LCDN1_0-14D-0	CUST