


TG4040

Ultra Soft Thermal Conductive Pad on rolls





Features

- Superior thermal conductivity
- Highly compressible
- Naturally tacky
- Low Shore 00 hardness
- Low oil bleed
- Electrically insulating

Applications

- Electronic components: IC / CPU / MOS
- LED / M/B / P/S / Heat Sink / LCD-TV / Notebook PC / PC / Telecom Device / Wireless Hub etc....
- DDR II Module / DVD Applications / Hand-Set applications etc...

Thermal Resistance V.S Pressure V.S Deflection




Properties

- REACH Compliant
- RoHS Compliant

Thermal Conductivity: 4.0 W/m.k
(W / m.k - Z Axis)

Hardness: 40 (Shore 00)
(Shore 00)



Testing sample thickness : 1.0 mm



In the thermal resistance vs pressure vs deflection charts TG4040 provides low thermal impedance. As the pressure increases the thermal impedance decreases. TG4040 provides good compliance and softness.

Property	TG4040	Unit	Test Method
Colour	Blue	-	Visual
Thickness (Available thickness range)	0.5 / 1 / 1.5 / 2	mm	ASTM D374
Roll Length / Width	50 - 320	Metres / mm	-
Thermal Conductivity	4	W/m.k	ASTM D5470
Flame Rating	V-0	-	UL 94
Dielectric Breakdown Voltage	15	kV/mm	ASTM D149
Weight Loss	<1	%	ASTM E595
Specific Gravity	2.8	g/cm ³	ASTM D792
Working Temperature	-45- +200	°C	-
Volume Resistance	>10 ¹²	Ohm-cm	ASTM D257
Elongation	100	%	ASTM D412
Tensile Strength	1	Kgf/cm ²	ASTM D412
Standard Shape	-	Sheet ones	-
Hardness	40	Shore 00	ASTM D2240

Available with an adhesive backing

